
# Linear Unit MRJ 40

The MRJ linear units have toothed belt drive and compact dimensions to provide high performance features such as high speed and good accuracy. For very high speeds, up to 10 m/s, the track rollers (journal bearings) of the type MRJ are particularly suitable.






The unit MRJ have a pre-tensioned steel reinforced AT polyurethane timing toothed belt. In conjunction with a zero-backlash drive pulley high moments with alternating loads with good positioning accuracy, low wear and low noise can be realized.
accuracy, low wear and low noise can be realized.


All parts in the profile are protected from dust and other contaminations. As corrosion-resistant protection strip is available as option.


Dimensions in mm.


**Modulus of Elasticity:** E = 70000 N / mm2
**Operating Temperature (°C):** 0 ~ +60 For operating temperature out of the presented range, please contact Rollco.
**Duty Cycle:** 100%
**Max. Acceleration (m/s²):** 50 (Optional, acceleration up to 70 m/s² possible if used without INOX seal strip)
**Max. Travel Speed (m/s):** 1.5 (Optional, travel speed up to 10 m/s possible if used without INOX seal strip)




1. Drive block with pulley
2. Corrosion-resistant protection strip (available also without protection strip)
3. AT polyurethane toothed belt with steel tension cords
4. Carriage with build in magnets
5. Aluminium profile-hard anodized
6. Track roller (journal bearing)
7. Two hardened steel round guide (58/60 HRC)
8. Central lubrication port, both sides
9. Tension end with integrated belt tensioning system









Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.


# Linear Unit MRJ 40





① Journal with or without keyway.


① All dimensions in mm. Drawings scales are not equal.

**TYPE 0**






**TYPE 1 L and 1 R**




① Journal with or without keyway.






**TYPE 2**





**MRJ 40**

A-A








① All dimensions in mm. Drawings scales are not equal.



Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

# Linear Unit MRJ 40









**Defining of the linear unit length**

**L = Effective stroke + 2 × Safety stroke + Lv + 32 mm** **Lv = 92 mm**

**Ltotal = L + 135 mm**




**Double-Carriage**





**L = Effective stroke + 2 × Safety stroke + Lv + A + 32 mm**

**Ltotal = L + 135 mm**

**A** ≥ Lv + 24 mm


Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

# General data




For lengths/stroke over the stated value in the table, please contact Rollco. Values for max. stroke are not valid for double carriage (equation of defining the linear unit length for particular size of the linear unit needs to be used).

For minimum stroke below the stated value In the table, please contact Rollco.

## Recommended values of loads

All the data of static and dynamic moments and load capacities stated in the table are theoretical without considering any safety factor. The safety factor depends on the application and its requested safety. We recommend a minimum safety factor (fs =5.0).

**Modulus of elasticity**
E = 70000 N / mm$^2$


| Designation | Carriage Length Lv (mm) | Load Capacity Cy (N) | Load Capacity Cz (N) | Dynamic Moment Mx (Nm) | Dynamic Moment My (Nm) |
|---|---|---|---|---|---|
| **MRJ 40** | 92 | 3400 | 1700 | 20 | 21 |

| Designation | Dynamic Moment Mz (Nm) | Max. Permissible Loads Forces Fpy (N) | Max. Permissible Loads Forces Fpz (N) | Max. Permissible Loads Moments Mpx (Nm) | Max. Permissible Loads Moments Mpy (Nm) | Max. Permissible Loads Moments Mpz (Nm) |
|---|---|---|---|---|---|---|
| **MRJ 40** | 25 | 1015 | 1090 | 13 | 14 | 7.6 |

| Designation | Moved Mass (kg) | Max. Repeatability (mm) | Max. Length Lmax (mm) | Max. Stroke (mm) | Min. Stroke (mm) |
|---|---|---|---|---|---|
| **MRJ 40** | 0.26 | ± 0.08 | 6000 | 5876 | 0 |


Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

# General data double carriage



A - Distance between carriages.

Max. travel speed and max. acceleration of linear unit with the corrosion-resistant protection strip is 1,5 m/s and 50 m/s² respectively.

The stated values are for strokes up to 500 mm. No load torque value increases with stroke elongation.

Max. acceleration (m/s²): 70


For acceleration over the stated value, please contact Rollco.

| Designation | Carriage version | Load Capacity Cy (N) | Load Capacity Cz (N) | Dynamic Moment Mx (Nm) | Dynamic Moment My (Nm) |
|---|---|---|---|---|---|
| **MRJ 40** | 2 | 6800 | 3400 | 40 | 1.7 × A (mm) |

| Designation | Dynamic Moment Mz (Nm) | Max. Permissible Loads Forces Fpy (N) | Max. Permissible Loads Forces Fpz (N) | Max. Permissible Loads Moments Mpx (Nm) | Max. Permissible Loads Moments Mpy (Nm) | Max. Permissible Loads Moments Mpz (Nm) |
|---|---|---|---|---|---|---|
| **MRJ 40** | 3.4 × A (mm) | 2030 | 2180 | 26 | 1.1 × A (mm) | 1.0 × A (mm) |


Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

# Drive data



Max. travel speed and max. acceleration of linear unit with the corrosion-resistant protection strip is 1,5 m/s and 50 m/s$^2$ respectively.

The stated values are for strokes up to 500 mm. No load torque value increases with stroke elongation.

Max. acceleration (m/s$^2$): 70

For acceleration over the stated value, please contact Rollco.

Mass calculation does not include mass of motor, reduction gear, switches and clamps.


| | |
|---|---|
| **Abs. stroke** | Absolute stroke [mm] |
| **A** | Distance between carriages [mm] |
| **nc** | Number of carriages |

| Designation | Max. Drive Torque Ma (Nm) | No Load Torque with Strip (Nm) | No Load Torque without Strip (Nm) | Pulley Drive Ratio (mm/rev) | Pulley Diameter |
|---|---|---|---|---|---|
| **MRJ 40** | 3.7 | 0.4 | 0.2 | 99 | 31.51 |

| Designation | Belt Type | Belt Width | Max. Force Transmitted by Belt (N) | Specific Spring Constant Cspec (N) | Planar Moment of Inertia Iy (cm$^4$) | Planar Moment of Inertia Iz (cm$^4$) |
|---|---|---|---|---|---|---|
| **MRJ 40** | AT3 | 20 | 235 | 225000 | 9.8 | 11.6 |


Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

# Mass and Mass moment



Max. travel speed and max. acceleration of linear unit with the corrosion-resistant protection strip is 1,5 m/s and 50 m/s$^2$ respectively.

The stated values are for strokes up to 500 mm. No load torque value increases with stroke elongation.

Max. acceleration (m/s$^2$): 70

For acceleration over the stated value, please contact Rollco.

Mass calculation does not include mass of motor, reduction gear, switches and clamps.

| | |
|---|---|
| **Abs. stroke** | Absolute stroke [mm] |
| **A** | Distance between carriages [mm] |
| **nc** | Number of carriages |

| Designation | Mass of Linear Unit (kg) | Mass Moment of Inertia ($10^{-5}$ kg m$^2$) | Planar Moment of Inertia Iy (cm$^4$) | Planar Moment of Inertia Iz (cm$^4$) | Moved Mass (kg) |
|---|---|---|---|---|---|
| **MRJ 40** | 1.25 + 0.0022 × (Abs. Stroke + (nc - 1) × A) + 0.26 × (nc - 1) | 9.3 + 0.0035 × (Abs. Stroke + (nc - 1) × A) + 6.5 × (nc - 1) | 9.8 | 11.6 | 0.26 |


Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.