

Rail

TLC43 - 3000 - 20 - 20 - NIC

Rail shape (T, U, or K)

(K is available for size 43 and 63)

Fixing holes (C or V)

Width of rail

Length of rail - maximum length in one piece (mm)

18: 2000, 28: 3200, 43: 4080, 63: 4080

Distance from end of rail to center of first hole

Distance from center of last hole to rail end

Surface treatment

Standard leave empty. NIC for nickle plated.

Note: For longer lengths, please contact Rollco

Mounted Rail and Slider

TLC43 - 2 - CSW43-150-2Z-A-T - 3000 - 20 - 20 - NIC

Rail type

No. of sliders on each rail

Slider type (CSW or N series)

Slider dimension

Slider body length

Roller protection shield type

Depending on slider type

Length of rail

Distance from end of rail to center of first hole

Distance from center of last hole to rail end

Surface treatment

Standard leave empty. NIC for nickle plated.

Note: For heavy preload please contact Rollco

Slider N...series

NTE 43

Slider type - available sizes:

18:	NT18	NU18	
28:	NTE28	NUE28	
43:	NTE43	NUE43	NKE43
63:	NTE63	NUE63	NKE63

Dimension (18, 28, 43, 63)

Slider CSW...series

CSW 43 - 150 - 2Z - A - T - NIC

Slider type

Dimension (18, 28, 43, 63)

Slider body length

Roller protection shield type (2Z, 2RS)

Configuration (A or B, only when necessary)

Type of wiper (T or U)

Surface treatment

Standard leave empty. NIC for nickle plated.