Belt conveyor with stand

BF40 - EIK - W250 - L5000 - 5 - RH2 - V - 0 - Kn8 - SL10 -	SR10 - A200 - B300 - D500 - E500 - 1	- 14 - Z
Size BF40 BF80		First leg distance (A)* (mm) O = Without stand
Type E = End drive M = Mid drive		Last leg distance (B)* (mm) O = Without stand
Knife edge IK = In Feed OK = Out Feed DK = Double / Both		Start height (D)* (mm) O = Without stand
Leave blank = None Width (W) (mm)		End height (E)* (mm) O = Without stand
Length (L) (mm)		Stand attachment type* O = Without stand 1 = Corner Brackets 2 = T-Plate
Speed 4, 5, 6, 8, 9, 12, 19, 25, 37 (m/min at 50 Hz) 0 = No drive unit included		Feet type* OO = None O1 = Swivel castor with total lock and bolt hole
Drive position R = Right L = Left		03 = L-Based Foot 04 = Angle Foot Al, adjustable 14 = Knuckle Foot
Drive orientation H1, H2, H3, H4, V1, V2, V3, V4 Leave blank = No drive unit		Customized Z = Yes
Belt type See website or contact us for further information.		
Belt profiles O = No 1 = Yes		*Note: A, B, D, E, stand attachment and feet will all have the value It is possible to have a stand without feet (00) but a stand
Tracking guides Kn6 (6x4x4) Kn8 (8x5x5) Kn10 (10x6x6) 2xKn6 2xKn8 2xKn10 Leave blank = None		
Conveyor guides left (SL) 10-100 (mm) 0 = None		
Conveyor guides right (SR) 10-100 (mm) 0 = None		

value 0 if the conveyor is defined without a stand. cand attachment must be selected.